

# Tred-MOR<sup>®</sup>

## CARPET CUSHION

### Tred-MOR<sup>®</sup> 2500 SPECIFICATIONS

#### SPECIFICATION DATA

Product Code:	BV0167
Product Name:	Tred-MOR <sup>®</sup> 2500
Traffic Classification:	Extra-Heavy
Material Weight:	100 oz./sq. yd.
Density:	33 lbs./cu. ft.
Thickness:	0.250"
Product Dimensions:	54" x 30' (15 sy.)
Mfg. Tolerances:	Width: +/-1% Thickness: +0.030/-0.015
Approx. Shipping Wt.:	95 lbs. per roll
Color:	Black
Material Content:	Made with Synthetic Rubber
Design Configuration:	Flat/Flat
Backing Top:	Spunbonded
Backing Bottom:	Poly-Tek
Antimicrobial:	Guardian <sup>™</sup>
Moisture Resistant:	98%
StainSTOP <sup>™</sup> :	Yes
Indoor Air Quality:	CRI Green Label Plus-certified

#### COMFORT AND DURABILITY

CLD PSI @ 25% Deflec. Min.:	7 (Method 601/12151)
CLD PSI @ 65% Deflec. Min.:	45 (Method 601/12151)
Breaking Strength PSI Length:	30 (Min. ASTM-D2646)
Breaking Strength PSI Width:	25 (Min. ASTM-D2646)
Compression Set:	15%

#### FLAME CERTIFICATION

Pill Test:	Pass (DOC-FF 1-70)
Smoke chamber:	Pass
Flooring Radiant Panel:	*

\*Not applicable to separate carpet cushion. Carpet must be tested in composition with cushion.



#### ACOUSTICAL PERFORMANCE

Impact Insulation Class (IIC):	63 (ASTM-492)
Sound Absorption (NRC):	0.35 (ASTM C423-81)

#### THERMAL INSULATION

R-Value:	0.340
K-Value:	0.730

#### OTHER

Meets Federal Spec.:	Class I (ZZ-00811B, Type I)
Toxicity:	No more toxic than wood – an accepted industry standard

#### PRODUCT FEATURES

Tred-MOR is the nation's premium commercial carpet cushion. It is synonymous with Dubl-Stik<sup>®</sup>, and is the benchmark by which all others are measured. Tred-MOR can also be used in conventional stretch-in installation, and is available with QuikLIFT<sup>®</sup> backing.

