

## Modular PVI®

Modular PVI® is a subfloor surface liner designed to be installed under modular carpet tile or modular composite tile with any backing type or any rigid-core tile or plank.

The product rolls out onto the subfloor, creating a sound and moisture barrier while also offering premium comfort. Modular PVI® also becomes a "clean-start" liner between the subfloor and the finished floor, leveling out any minor irregularities. It can be installed on, above, or below grade.



Clean-start  
Subfloor surface lining



Acoustical barrier  
Passive vibration isolation



Breathable moisture barrier  
with antimicrobial



Anti-fatigue comfort



No glue • single glue  
Double glue




Radiant heat-friendly

### APPLICATIONS

- Hospitality
- Casinos
- Campus living
- Corporate
- Senior living
- Multi-family
- Indoor public space
- Convention centers/ballrooms

### PRODUCT SPECIFICATION DATA

Product code:	BV0278
Product name:	Modular PVI®
Color:	Bright green
Material content:	100% synthetic rubber
Traffic classification:	Class III extra heavy
Material weight:	62 oz./sq. yd.
Density:	33 lbs./cu. ft.
Thickness:	4.00 mm (5/32")
Roll weight:	124 lbs.
Roll dimensions:	4'6" x 60' (30 sq. yd.) 270 sq. ft./roll



### COMFORT & DURABILITY (ASTM D3676, D3574)

Compression set @ 50%:	34.6%
Indentation force deflection @ 25%:	344.6 lbs. of force
Indentation force deflection @ 65%:	2,828 lbs. of force

### GREEN CREDENTIALS (CRI Standards)

Recyclable:	100% recyclable
Indoor air quality:	CRI Green Label certified
VOC emissions:	Pass-Calif. section 01350

### FLAME CERTIFICATION (DOC-FF 1-70)

Pill test:	Pass
Smoke chamber:	Pass
Radiant panel:	Composite test with carpet tile or rigid core

### MOISTURE RESISTANCE (ASTM E96)

Resistance to topical liquid:	100%
Vapor permeance from slab:	Class III Vapor semi-permeable

### ACOUSTICAL PERFORMANCE (ASTM E90, E492, E2179)

	6" Concrete Bare Slab	2' x 10' Wood Frame 3/4" Gypsum
Impact insulation class (IIC):	65	55
Delta IIC (ΔIIC):	32	N/A
Sound transmission class (STC):	52	55