


# SCI® Acoustic Underlayment

# **dBarrier™** Luxury Vinyl Underlayment

- Provides significant reduction to impact noise in the room and floor below
- High density for unmatched support under interlocking luxury vinyl flooring
- Can be used over most substrates – on, above, or below grade
- Installs quickly and easily
- Guardian™ antimicrobial inhibits the growth of mold, mildew, and odor-causing bacteria
- Recommended by the Radiant Professionals Alliance for use over in-floor heating
- Hypoallergenic

## SPECIFICATIONS

Product Code:	BV0340
Composition:	Made of High-Density Synthetic Rubber
Density:	62 lbs/ft <sup>3</sup> or 42 oz/yd <sup>2</sup>
Thickness:	0.056" (1.42 mm)
R-Value:	0.02
Moisture Barrier:	N/A*
Color:	Red
Castor Durability Test:	Passes 25,000 Cycles**
Dimensions:	54" x 44.44'
Ft <sup>2</sup> /Roll:	200
Yd <sup>2</sup> /Roll:	22.22
Roll Weight:	58 lbs.



## ACOUSTICAL PROPERTIES

Impact Insulation Class (IIC)***	66
ΔIIC	22
Sound Transmission Class (STC)***	63

## PROTECTION

Indoor Air Quality:	CRI Green Label Plus-Certified
Antimicrobial:	Yes
Warranty:	Limited

For use under

- Luxury vinyl tile/plank
- Rigid composite
- Other premium resilient flooring
- Laminate
- Engineered hardwood
- Solid hardwood



\*Separate moisture barrier should be used on slab foundation and below-grade installation

\*\*Passes Castor Durability Test for 25,000 cycles when tested under minimum of 3 mm double-glued luxury vinyl plank and minimum 3.2 mm floating-click

\*\*\*When tested with floor-ceiling assembly

IIC: ASTM E492-09/ASTM E989-06

ΔIIC: ASTM E2179-03

STC: ASTM E90/ASTM E413-10



**SCI®**  
**Sponge Cushion, Inc.**  
A Leggett & Platt, COMPANY  
INCORPORATED

902 Armstrong Street | P.O. Box 709 | Morris, IL 60450 | 800.435.4062 | 815.942.2300 | FAX: 815.942.9636  
Sponge-Cushion.com | LPHospitality.com

U.S.G.B.C. Member Logo is a trademark owned by the U.S. Green Building Council and is used by permission.

©2017 Leggett & Platt, Incorporated | MTL1153\_21332\_0217